



GENERAL PRODUCT SPECIFICATION

Item No.	CH200
-----------------	--------------

Date	12-09-13	Replaces	7-11-13	No. Pages	1
-------------	----------	-----------------	---------	------------------	---

Product Description:

Style	Pads; perforated on centerline for dividing in half for smaller applications
Item Size (each)	15" x 19"
Color	Yellow
Composition	100% Polypropylene
Structure	A 3-ply non-woven mat of randomly oriented meltblown micro-fibers [2-10 micron diameters] One side having a Yellow lint & abrasion resistant spunbond cover-stock (non-woven, continuous filaments randomly oriented and thermally point bonded [15-30 micron diameters]). Other side is meltblown Coverstock The (3) plies are secured together with bonded dimpling.
Technology	Spunbond , Meltblown & Meltblown Coverstock
Absorbency	Universal (Hydrophilic + Oleophilic)
Bonding	Mechanical entanglement + Bonded (staggered pattern)

Intended Application	Abrasion Resistant, Lint Resistant, & Chemical Resistant Sorbent for Oil or Solvent Base Liquids
-----------------------------	--

Absorbency Capacity	28 gal. per bale (saturated; medium viscosity-18x)
----------------------------	--

Packaging Description:

Package configuration	1-Case	Pkg. Weight	16-lbs (15.3)
Items per Package	200-Pads/Case	Pkg. Dimensions	16" x 20" x 20"H
Container type	Case		

Physical Properties:

<u>Parameter</u>	<u>SPC Test Method</u>	<u>Units</u>	<u>Nominal</u>	<u>(+/-)Tolerance</u>
Basis Weight	SPCTM-002A	G/M2	190	20
Caliper	SPCTM-003A	mils	170	17
Absorbency** (med. Oil)	SPCTM-004B	gL/gS	13	2
Tensile Strength	SPCTM-007	lbs	5	1
Color	Visual	-----	Yellow	per standard

The above properties are "nominal" values used for PROCESS CONTROL when the product is produced and/or inspected. Performance "nominals" may vary depending upon the specific application, and/or the environment being applied, stored, or shipped.

**** The "Absorbency" Spec and "SPCTM004" test method is based on the protocol of ASTM F726, using SAE20 non-detergent as the Oil Type, medium viscosity.**

Attributes	Product will be free of foreign material contamination, rips, holes, and tears.
Labeling	Each package to be clearly labeled with Company Name, Address, Item No., Date, and/or Package Code (Bar Code).
Certification	Make no changes in basic process or composition without notifying customer. Claims for non-conformance of goods must be made within 60-days of delivery.