



GENERAL PRODUCT SPECIFICATION

Item No.	CH303
-----------------	--------------

Date	11-6-13	Replaces		No. Pages	1
-------------	---------	-----------------	--	------------------	---

Product Description:

Style	Blanket Roll; high strength perforation down the middle for the 15" wide dimension, & cross-wise for the 15" long dimension
Item Size (each)	30" wide by 300' long (480 Pads)
Color	Yellow
Composition	100% Polypropylene
Structure	A 3-ply non-woven mat of randomly oriented meltblown micro-fibers [2-10 micron diameters] One side having a Yellow lint & abrasion resistant spunbond cover-stock (non-woven, continuous filaments randomly oriented and thermally point bonded [15-30 micron diameters]). Other side is meltblown Coverstock. The (3) plies are secured together with bonded dimpling.
Technology	Spunbond , Meltblown & Meltblown Coverstock
Absorbency	Hydrophilic + Oleophilic
Bonding	Bonded (staggered pattern) + Mechanical entanglement

Intended Application	Abrasion Resistant, Lint Resistant, & Chemical Resistant Sorbent for Oil or Solvent Base Liquids
-----------------------------	--

Absorbency Capacity	80 gal. per bale (saturated; medium viscosity-12x)
----------------------------	--

Packaging Description:

Package configuration	Bale	Pkg. Weight	45-lbs (44.5)
Items per Package	1-Roll/Bale	Pkg. Dimensions	19" Dia. x 31" H
Container type	Polybag + Twist tie		

Physical Properties:

<u>Parameter</u>	<u>SPC Test Method</u>	<u>Units</u>	<u>Nominal</u>	<u>(+/-)Tolerance</u>
Basis Weight	SPCTM-002	G/M2	250	25
Caliper	SPCTM-003	mils	180	20
Absorbency** (med. Oil)	SPCTM-004B	gL/gS	12	2
Tensile Strength	SPCTM-007	lbs	30	3
Color	Visual	-----	Yellow	per standard

The above properties are "nominal" values used for PROCESS CONTROL when the product is produced and/or inspected. Performance "nominals" may vary depending upon the specific application, and/or the environment being applied, stored, or shipped.

**** The "Absorbency" Spec and "SPCTM004" test method is based on the protocol of ASTM F726, using SAE20 non-detergent as the Oil Type, medium viscosity.**

Attributes	Product will be free of foreign material contamination, rips, holes, and tears.
Labeling	Each package to be clearly labeled with Company Name, Address, Item No., Date, and/or Package Code (Bar Code).
Certification	Make no changes in basic process or composition without notifying customer. Claims for non-conformance of goods must be made within 60-days of delivery.