



TECHNICAL DATA SHEET

Order reference	SF1
Article number	813796

Date	4-11-11	Replaces	3-01-09	No. Pages	1
-------------	---------	-----------------	---------	------------------	---

Product Description:

Style	50 kg Microfibres
Item Size (each)	3 mm strands, in 10 cm lengths
Color	White
Composition	100% Polypropylene
Structure	Nonwoven strand of randomly oriented Micro-fibers [4-10 micron diameters]
Technology	Meltblown, 1-ply
Absorbency	Hydrophobic + Oleophilic
Bonding	Mechanical entanglement + Shredding

Intended Application	Various. Anything from Filtration to Spill cleanup.
-----------------------------	---

Absorbency Capacity	868 l per carton (saturated; medium viscosity- 15x)
----------------------------	---

Packaging Description:

Package configuration	1-Carton	Pkg. Weight	54,5 kg (50kg)
Items per Package	1-Carton (50kg)	Pkg. Dimensions	1.2 m x 0.8 x 1 m
Container type	Carton		

Physical Properties:

<u>Parameter</u>	<u>SPC Test Method</u>	<u>Units</u>	<u>Nominal</u>	<u>(+/-)Tolerance</u>
Basis Weight	SPCTM-002	G/M2	280	28
Caliper	SPCTM-003	mm	3.2	0.3
Absorb.** (med. oil)	SPCTM-004B	gL/gS	15	1.5
Color	Visual	-----	White	per standard

The above properties are “nominal” values used for **PROCESS CONTROL** when the product is produced and/or inspected. Performance “nominals” may vary depending upon the specific application, and/or the environment being applied, stored, or shipped.

** The "Absorbency" Spec and "SPCTM004" test method is based on the protocol of ASTM F726, using SAE20 non-detergent as the Oil Type, medium viscosity.

Attributes	Product will be free of foreign material contamination, rips, holes, and tears.
Labeling	Each package to be clearly labeled with Company Name, Address, Item No., Date, and/or Package Code (Bar Code).
Certification	Make no changes in basic process or composition without notifying customer. Claims for non-conformance of goods must be made within 60-days of delivery.